

**COB-EX-0080      HAZARDOUS LIGHTING SERIES 80 WATTS**

<b>Delivered Lumens</b>	11,200 lm
<b>Wattage</b>	80 W
<b>Delivered Efficacy</b>	140 lm/W
<b>Voltage</b>	AC100-277V
<b>Available Color Temp.</b>	3000-5000K
<b>CRI</b>	>70
<b>Optional CRI*</b>	>82
<b>Beam Angle</b>	15°, 40°, 60°, 80°, 120°, Type 2, Type 3
<b>Weight**</b>	7.3 kg (16.1 lb.)
<b>Operating Temperature</b>	-40° to 50°
<b>Dimensions</b>	210mm×400mm×161mm (8.3"×15.7"×6.3" )
<b>Dimming</b>	n/a
<b>Material</b>	Copper-free aluminum, Shock and vibration resistant tempered glass
<b>Warranty</b>	5 Years
<b>Standard Installation</b>	Surface, Wall, Suspension, Pole, Pole top
<b>Listing</b>	Class 1, Division 2 – Groups A,B,C,D

\*>82 CRI is standard only for 3000K CCT

\*\*Fixture weights specified are displayed for the standard configuration for the model. Weight fluctuation will be dependent on desired configuration.

\*\*\*Other features, not listed, can be added per customer request.