

**SLD- LN- 0060****LI NEAR SERI ES 53 WATTS**

<b>Del i ver ed Lumens</b>	<b>7, 900 l m</b>
<b>Watt age</b>	<b>53 W</b>
<b>Del i ver ed Eff i cacy</b>	<b>149 l m<sup>2</sup> W</b>
<b>Vol t age</b>	AC120/ 277/ 347V
<b>Avai l abl e Col or Temp.</b>	3000- 6000K
<b>L70 ( TM21)</b>	100, 000 hour s
<b>CRI</b>	>80
<b>Opt i onal CRI</b>	
<b>Beam Angl e</b>	120°
<b>Wei ght **</b>	2. 57 kg ( 5. 67 l b)
<b>Oper at i ng Temper at ur e</b>	- 40° t o 55° C
<b>Di mensi ons</b>	1170mm x 100mm x 60mm
<b>Di mmi ng</b>	TBD
<b>Mat er i al</b>	Whi t e Powder - coat ed Al umi num Ext r usi on, UL94- V0 ABS Pl ast i c End Caps, Hi gh St rengt h
<b>Warr ant y</b>	5 year s
<b>Mbunt i ng</b>	on ceili ng/ wall , or by suspensi on ki t
<b>Opt i ons***</b>	Mbt i on Sensor , I mpact prot ect i on

\*\*Fixture weights specified are displayed for the standard configuration for the model. Weight fluctuation will be dependent on desired configuration.

\*\*\*Other features, not listed, can be added per customer request.