

**SOL-G2-D200****SOL-G2 SERIES 176 WATTS**

<b>Delivered Lumens</b>	28,160 lm
<b>Wattage</b>	176 W
<b>Delivered Efficacy</b>	160 lm/W
<b>Voltage</b>	AC100-480V
<b>Available Color Temp.</b>	2700-6500K
<b>L70 (TM21)</b>	250,000 hours
<b>CRI</b>	>80
<b>Optional CRI</b>	>90
<b>Beam Angle</b>	120°
<b>Weight**</b>	7.00 kg (15.5 lb.)
<b>Operating Temperature</b>	-40° to 60°C
<b>Dimensions</b>	Ø600mm×370mm (Ø23.6"×14.6")
<b>Dimming</b>	0-10V Optional
<b>Material</b>	Aluminum, Sheet Metal, UL94-5VA PC Lens
<b>Warranty</b>	5 Years ; extendable to 10 years
<b>Mounting</b>	Installation on 4" junction box, pendant conduits, on ceiling surface, or by cable suspension
<b>Options***</b>	0-10Vdc Dimming , In-fixture Motion Sensor, Emergency Back up Lighting, Surge Protection, Wireless Control, Impact protection

\*\*Fixture weights specified are displayed for the standard configuration for the model. Weight fluctuation will be dependent on desired configuration.

\*\*\*Other features, not listed, can be added per customer request.